

§ 412.22

Weather Service in Technical Paper Number 40, "Rainfall Frequency Atlas of the United States", May 1961, and subsequent amendments, or equivalent regional or state rainfall probability information developed therefrom.

(f) The term *dry lot* shall mean a confinement facility for growing ducks in confinement with a dry litter floor cover and no access to swimming areas.

(g) The term *wet lot* shall mean a confinement facility for raising ducks which is open to the environment with a small portion of shelter area, and with open water runs and swimming areas to which ducks have free access.

§ 412.22 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

(a) Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

Effluent characteristic	Effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed—
	Metric units (kg/1,000 ducks)	
BOD ₅	1.66	0.91
Fecal coliform	(¹)	(¹)
	English units (lb/1,000 ducks)	
BOD ₅	3.66	2.00
Fecal coliform	(²)	(²)

¹ Not to exceed mpn of 400/100 ml at any time.

² See above (not typically expressed in English units).

(b) [Reserved]

[39 FR 5706, Feb. 14, 1974, as amended at 60 FR 33951, June 29, 1995]

§ 412.23 [Reserved]

§ 412.24 Pretreatment standards for existing sources.

The pretreatment standards under section 307(b) of the Act for a source within the ducks subcategory which is a user of a publicly owned treatment works and a major contributing indus-

40 CFR Ch. I (7–1–00 Edition)

try as defined in 40 CFR part 128 (and which would be an existing point source subject to section 301 of the Act, if it were to discharge pollutants to the navigable waters), shall be the standard set forth in 40 CFR part 128, except that, for the purpose of this section, 40 CFR 128.121, 128.122, 128.132, and 128.133 shall not apply. The following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

Pollutant or pollutant property	Pretreatment standard
Fecal coliform	No limitation.
BOD ₅	Do.

[40 FR 6440, Feb. 11, 1975]

§ 412.25 Standards of performance for new sources.

(a) Subject to the provisions of paragraph (b) of this section, the following standards of performance establish the quantity or quality of pollutants or pollutant properties which may be discharged by a source subject to the provisions of this subpart: There shall be no discharge of process waste water pollutants to navigable waters.

(b) Process waste pollutants in the overflow may be discharged to navigable waters whenever rainfall events, either chronic or catastrophic, cause an overflow of process waste water from a facility designed, constructed and operated to contain all process generated waste 24-hour rainfall event for the location of the point source.

§ 412.26 Pretreatment standards for new sources.

The pretreatment standards under section 307(c) of the Act for a source within the ducks subcategory, which is a user of a publicly owned treatment works (and which would be a new source subject to section 306 of the Act, if it were to discharge pollutants to the navigable waters), shall be the standard set forth in part 128, of this chapter, except that, for the purpose of this section, § 128.133 of this title shall be amended to read as follows: